

ARMY RESEARCH LABORATORY



Pulsed Power, Plasma, and Interior Ballistic Simulations for Application to Electrothermal- Chemical Guns

Gary L. Katulka
William F. Oberle
Gloria P. Wren
U.S. Army Research Laboratory

Jeffrey Okamitsu
Neale A. Messina
Lockheed Martin Defense Systems

ARL-TR-1070

MARCH 1996

Approved for public release; distribution is unlimited.

DTIC QUALITY INSPECTED 2

19960408 137

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1996		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE Pulsed Power, Plasma, and Interior Ballistic Simulations for Application to Electrothermal-Chemical Guns				5. FUNDING NUMBERS PR: 1L1622618AH75	
6. AUTHOR(S) Katulka, G.L.; Oberle, W.F.; Wren, G.P.; Okamitsu, J.; Messina, N A.					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons Technology Directorate Aberdeen Proving Ground, MD 21010-5066				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons Technology Directorate Aberdeen Proving Ground, MD 21010-5066				10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARL-TR-1070	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Under U.S. Army Research, Development, and Engineering Center contract DAAA21-93-D1003 (subcontract GC-2539-45-93-024), Princeton Combustion Research Laboratories (PCRL) recently completed the development of a PC-based, end-to-end electrothermal-chemical (ETC) gun ballistic simulation code called the pulsed power plasma interior ballistics (PPIB). PPIB is a time-dependent, lumped parameter, electrothermal-chemical gun ballistic simulator which has a one-dimensional plasma submodel. The PPIB code is used to simulate the three main subsystems of the overall ETC gun system, including the pulse power subsystem, the plasma cartridge, and the interior ballistic process. PPIB is a linkage of three well-established systems models: (1) P2SIM for pulse power, developed by PCRL to model electric gun pulse power supplies, (2) the plasma cartridge code of Powell and Zielinski from the U.S. Army Research Laboratory (ARL), and (3) the latest version of the interior ballistics code IBHVG2 from ARL. PPIB is written in American National Standards Institute (ANSI) standard formula translator (FORTRAN) and is designed to run on any 386, 486 or Pentium-based PC platform. The code has been validated against a 4-MJ pulsed power system, 30-mm ETC plasma experiments, and plasma capillary calculations from the stand-alone Powell code, all of which are presented here. In addition, results obtained for high energy plasma simulations are provided. Included in this study are 1) the electrical behavior and transfer efficiencies of various plasma capillary tubes; 2) the amount of energy partitioned to each of the constituents within the plasma such as internal, kinetic, and work energy; and 3) the radiant energy partitioning of the plasma inside the capillary tube during the electrical discharge. The study is concluded with an estimate of the overall energy delivered for the entire process of power supply discharge to electrical plasma generation and radiation for a given test case.					
14. SUBJECT TERMS electric gun interior ballistics pulsed power electrothermal-chemical plasma				15. NUMBER OF PAGES 40	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT		

INTENTIONALLY LEFT BLANK

ACKNOWLEDGMENTS

The authors of this work acknowledge the efforts of Dr. Richard Beyer, Mr. James DeSpirito, and Dr. Michael McQuaid from the U.S. Army Research Laboratory for their careful review of this manuscript. Also, the contributions of Drs. John Powell and Kevin White from ARL, in the form of technical analysis and computations, are greatly appreciated.

INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

		<u>Page</u>
	LIST OF FIGURES	vii
	LIST OF TABLES	ix
1.	INTRODUCTION	1
1.1	Pulsed Power Plasma Interior Ballistic (PPIB) Code Description	1
1.2	Technical Methods Employed	2
2.	SIMULATIONS	4
2.1	Validation of P2SIM (pulsed power simulations)	4
2.2	Validation of the Plasma Model	5
2.3	High Energy ETC Plasma Calculations	6
3.	SUMMARY	10
	REFERENCES	13
	APPENDIX	
	A. INPUT DECKS	15
	DISTRIBUTION LIST	21

INTENTIONALLY LEFT BLANK

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Validation of PPIB With Microcap III Showing Delivered Electrical Power and Energy to a 120-m Ω Resistive Load.	5

INTENTIONALLY LEFT BLANK

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Comparison of PPIB and Powell Plasma Model Simulations	7
2. Plasma Energy Partitioning for Three Test Cases With Varied Radii	8
3. Percentage of Delivered Electrical Energy From the Pulsed Power Supply to Plasma Components of Internal, Kinetic, and Work Energies	9
4. Black Body Radiation Prediction for Three Plasma Test Cases	9

INTENTIONALLY LEFT BLANK

1. INTRODUCTION

The electrothermal-chemical (ETC) propulsion concept represents an advanced weapon technology in which a conventional gun tube and combustion chamber are used to accelerate a projectile. The system differs, however, from typical cannon weaponry in that it relies upon the discharge of electrical energy from a power supply through an insulating capillary tube forming an electrical plasma, which is injected into the gun chamber for ignition and combustion control of propellant. The discharge forms an arc that generates a hot, high pressure, low molecular weight plasma source. The high temperature plasma in the interior of the capillary causes ablation and vaporization of surrounding insulation, which is enveloped by hot gaseous material and sustains the original plasma arc. The energetic plasma is then injected into a bed of chemical propellant in the gun combustion chamber. The input plasma is used to first ignite the propellant and later, it is proposed to drive and control the combustion process of the gun. It is hypothesized that control of the combustion could result from burn rate modifications of the propellant as a result of interaction with the high temperature plasma.¹ The effects of electrical plasmas on burn rates of some JA2 sample propellants have been investigated in closed chamber ETC experiments at the U.S. Army Research Laboratory (ARL). The results, although preliminary and still being studied, indicated potential burn rate increases compared to those in conventional JA2 tests.² Because of the importance of the plasma source with regard to the ETC technology, it was decided to examine some of the basic properties of plasma generation as well as characteristics of the plasma itself, which are described later in this report.

1.1 Pulsed Power Plasma Interior Ballistic (PPIB) Code Description

PPIB is a time-dependent, lumped parameter, end-to-end computer model of an ETC gun system.³ PPIB simultaneously models the performance of the pulse power system, the plasma cartridge, and the interior ballistics of a solid propellant ETC gun. It is a linkage of three established models: (1) P2SIM,⁴ (2) Powell's plasma cartridge code,⁵ and (3) IBHVG2,⁶ for interior ballistic calculations. The pulse power code (P2SIM) is linked to the plasma cartridge code by having the plasma cartridge act as the pulse power system load. Any change in the output of the pulse power system (e.g., increase in current) is directed into the plasma cartridge and will cause a change in the state of the plasma. Any variation in the plasma (e.g., change in temperature) will be reflected in the pulse power system as a change in plasma cartridge resistance, thereby altering the pulse power system load. Similarly, any change in the plasma discharge into the gun will cause a concurrent change in the combustion of the gun propellant, the gun chamber pressure, and ultimately the projectile. A change in the combustion of the gun propellant is reflected back into the plasma cartridge as a change in the pressure inside the

cartridge, which, during certain conditions (e.g., unchoked flow) affects the output of the cartridge and the state of the plasma. This will also affect the thermodynamic properties of the plasma. Obviously, this change in plasma property is reflected back to the pulse power system as a change in the plasma cartridge resistance.

1.2 Technical Methods Employed

Given the plasma cartridge length and radius, its resistance is given by

$$R = \frac{l}{\sigma \pi a^2} \quad (1)$$

in which l is the length of the cartridge, a is the radius, and σ is the conductivity of the plasma. The conductivity is given by

$$\sigma = \frac{n_e e^2}{m_e (\nu_{en} + \nu_{ei})} \quad (2)$$

in which n_e is the density of electrons in the plasma, e is the electron charge, m_e is the electron mass, ν_{en} is the collision frequency for electrons and neutral atoms, and ν_{ei} is the collision frequency for electrons and ions. The resistance value from Equation 1 is the load resistance for the pulse power part of PPIB. The current density J in the plasma is given by

$$J = \frac{I}{\pi a^2} \quad (3)$$

in which I is the current from the pulse power system flowing into the plasma cartridge. The current density is used in the energy equation (Equation 3 in Reference 4) for the plasma cartridge. This equation is

$$\frac{\partial}{\partial \xi} \left[\rho \omega \left(U + \frac{1}{2} \omega^2 \right) \right] + \frac{\partial}{\partial \xi} (\wp \omega) = \frac{J^2}{\sigma} L - \frac{\partial q_z}{\partial \xi} - 2 \frac{q_{rs} L}{a} \quad (4)$$

in which \wp , ρ , and w are the pressure, density and flow speed; q_z and q_{rs} are the longitudinal and radial heat fluxes; U is the internal energy of the plasma (per unit mass) and ξ is the dimensionless parameter z/L .

The linkage of the P2SIM and Powell codes was accomplished by using P2SIM's "user-defined load" capability with Powell's code being the load. In addition, with PPIB, the user has

the option of including the plasma cartridge parasitic inductance, the cartridge lead resistance, and the power cable resistance.

To simulate the start of the event, an exploding wire is simulated in the model. The expression for temperature of the exploding wire is based on the power in the wire and the assumption that the energy leaves the wire as thermal (black body) radiation, i.e.,

$$T = (I^2 R / kA)^{0.25} \quad (5)$$

in which A is the surface area of the wire and k is the Stefan-Boltzmann constant. To simulate the coupling of the radiant energy from the exploding wire to the plasma liner, the absorptivity of the plasma liner is also included as a model parameter.

The coupling between the Powell plasma cartridge code and IBHVG2 is likewise very straightforward. The plasma energy, determined from the time integral of input plasma power, is added directly to the energy balance equation. This equation is modified for an ETC gun system model and is given as

$$\sum_{ij} m_{ij} c_{vij} T_{fij} + \sum_k m_k c_{pk} T_{pk} + \int_0^t P dt = \left[\sum_{ij} m_{ij} c_{vij} + \sum_k m_k c_{pk} \right] T_{mean} + L \quad (6)$$

in which the first sum is over every surface j of each propellant charge i ; the second sum is over every species in the plasma. The propellant gas mass is given by m_{ij} , c_v is the specific heat at constant volume for the propellant gases, and T_f the flame temperature of the propellant. The plasma species mass is m_k , c_p is the specific heat of the plasma species, and T_p is the plasma temperature. P is the plasma power injection term and the integral is from the start of the event until the time, t . T_{mean} and L are the mean temperature of the system and the energy loss terms, respectively.

The plasma output power, P , is comprised of three different terms. The first is the term attributable to the thermal internal energy of the plasma and is given by the product of the plasma specific internal energy at the discharge orifice, e (in J/kg), and the mass flux rate, F (in kg/s), at the discharge orifice,

$$P_1(t) = e(t)F(t) \quad (7)$$

The second term is the kinetic energy of the plasma and is given as

$$P_2(t) = 0.5 F(t)(v(t))^2 \quad (8)$$

in which $v(t)$ is the gas linear speed.

The third term is the work done against the gas pressure and is given as

$$P_3(t) = P_o A v(t) \quad (9)$$

with P_o being the pressure at the discharge orifice and A the orifice area. The total power is then the sum of these three terms.

There is no attempt to calculate the effects of incomplete mixing and transfer of energy to the propellant combustion gas. Therefore, the model will tend to overestimate the amount of energy transfer. Aside from a complete treatment of the mixing of plasma and propellant gas, which is beyond the scope of this project, the only way to accommodate incomplete mixing as well as to control the contribution from the terms in Equations 8 and 9 is to introduce a set of energy "coupling" factors. There is one factor for each power term. A coupling factor of one (1) denotes perfect coupling of the plasma power for that contribution to the combustion gas, while a factor of zero denotes no coupling. The default values in the program are 1, 0, and 0 for Equations 7, 8, and 9, respectively, which indicates total transfer of internal plasma energy into the gun chamber and no energy transferred from kinetic and work energy components.

The execution of the code is similar to that of P2SIM. However, termination of the event will be controlled by IBHVG2, which in most cases occurs at projectile exit. Data are input to the program via three separate data files: one for pulse power, one for plasma, and one for IBHVG2. The pulse power input is virtually identical to the P2SIM input deck, and the plasma input is virtually the same as the original Powell code. The interior ballistic input deck is similar to an ETC IBHVG2 deck. Output data from the end-to-end PPIB code consist of three data files, one for each subsystem.

2. SIMULATIONS

2.1 Validation of P2SIM (pulsed power simulations)

P2SIM was validated through comparisons with simulations obtained from electronic circuit analysis software. For this task, Microcap III (Spectrum Software) was used as a standard to predict the performance of an electric gun type pulsed power supply discharging into a fixed resistive load.⁷ Although the fixed resistive load does not model the exact electrical behavior of the electric gun plasma load, it does provide a reasonable approximation of the electrical behavior of the power supply. The results of simulations from P2SIM and Microcap III for a 4-MJ pulsed power supply configured from a network consisting of capacitors, inductors, switches, and other components are given in Figure 1, where the two sets of predicted curves are within 5% of perfect agreement. Other validation exercises have been performed for

other power supply configurations that are not detailed here but were performed under contract to the U.S. Army.⁸ Included among the types of power supply configurations that can be modeled by PPIB are compulsators and homopolar generators as well as capacitor-based pulse-forming networks (PFNs) as illustrated in this report. The input deck for P2SIM used to generate the data in Figure 1 is given in Appendix A, Part 1.




Figure 1. Validation of PPIB with Microcap III Showing Delivered Electrical Power and Energy to a 120-m Ω Resistive Load.

2.2 Validation of the Plasma Model

To validate the pulse power and plasma linkage, experimental data were compared to predictions from the linked code. These data were taken from test firings from the ARL five-module PFN with the capacitors charged to 7 kV, which was discharged into an open air type plasma capillary. The switch firing times were set for a short pulse at 0 s, 40 s, 80 s, 120 s, and 180 s. The plasma cartridge dimensions used were length 10.92 cm (4.3 inches) and inner diameter 0.95 cm (0.375 inch). The model input included the pulse power parameters (capacitor voltages and switch times), the plasma cartridge parameters (capillary radius and length), the number of iterations per time step and the physics parameters of the plasma (partition function data, ionization potentials, etc.). The PFN and plasma cartridge input decks for these calculations are given in Appendix A, Parts 2 and 3. For the purpose of validation, the measured load current was compared to the current predicted by the model. The agreement between the two current waveforms is quite good, with the model slightly over-predicting the peak current value at an earlier time than the actual data. The predicted peak current is 64.3 kA, occurring at

approximately 237 s, while the measured peak is 61.5 kA, occurring at 280 s. The reason for the difference in peak values is probably attributable to added resistive losses in the actual system, and the difference in time is most likely attributable to inductive effects in either the pulsed power/plasma system or in the measurement apparatus.

In addition, the linked plasma model was further validated by comparing output data with the stand-alone Powell plasma model. For these simulations, the model input parameters adjusted were the current magnitude, capillary radius, and capillary length. The predicted bulk plasma temperature and plasma resistance from the two models are shown in Table 1. The conductivity model assumed for these calculations is that of Kurilenkov and Valuev,⁹ and a surface temperature lower than the bulk plasma temperature is also assumed. Note that the linked plasma model in PPIB incorporates the entire end-to-end code including P2SIM and IBHVG2. Since it is necessary to test the plasma model in a condition independent from the interior ballistic portion of the code, a large chamber volume containing a small propellant charge was modeled by the IBHVG2 subroutine. This allowed for a choked flow condition in the plasma model for the duration of the calculation, which was the case for the stand-alone model. The results of the calculations from the two codes are given in Table 1, where the current magnitude varies from 16 kA to 287 kA. Once again, the agreement between the two models is reasonably good with the largest discrepancy of about 13% occurring for the resistance in the 150-kA case. One possible explanation for this discrepancy is the fact that the Powell model as used here provides output for a single input current data point, whereas the PPIB code predicts output for the entire current waveform. The PPIB code is time dependent whereas the Powell model used here is a steady state code. The output data from PPIB and Powell are compared at a single current data point used in the Powell code. This means that PPIB, in most cases, will have calculated plasma data for many points before reaching the current level assumed in the Powell code. Obviously, any time-dependent changes in capillary conditions could account for errors of this size since the output data are generally a strong function of the initial input parameters. Once again, a sample input deck for PPIB is provided in Appendix A, Part 4.

2.3 High Energy ETC Plasma Calculations

The Powell plasma model was used to characterize the energy partitioning of the plasma as a result of a discharge from a portion of a 4-MJ pulsed power supply, specifically a 2-MJ portion of the full 4-MJ power supply.¹⁰ The results from the calculations are given in Table 2 for each of three cases in which the capillary radius is varied from 1.92 to 7.00 mm for a given current amplitude--in this case, 75 kA. The plasma code, which is described in great detail in

Reference 4, predicts the plasma internal, kinetic, and work energies based on the input parameters of plasma capillary radius, length, and input current magnitude. The code was used here to determine the amount of energy contained in each of the three energy components (internal, kinetic, work) for a realistic power supply configuration and with realistic dimensions. The capillary radius is fixed at 11.84 cm (sized for a 120-mm tank cannon application). The internal energy consists of the energy required to vaporize, dissociate, and ionize the plasma material, thermal energy of the plasma, and electronic excitation energy. The kinetic energy is associated with the movement of plasma through the capillary tube ($1/2 m v^2$), while the work energy is the energy against pressure in the capillary (P/p). As seen in the data of Table 2, for all cases, the majority of energy is contained in the internal energy component, with the smallest component being kinetic energy. The general trend is for a decrease in internal energy and an increase in kinetic and work energies as the capillary radius is decreased, which seems reasonable since the capillary pressure rises rapidly with decreasing capillary radius. However, the internal energy is fairly stable over the range of radii examined with only 8.5% change from smallest to largest capillary.

Table 1. Comparison of PPIB and Powell Plasma Model Simulations (with Kurilenkov-Valuev conductivity model and surface temperature assumption)

<u>INPUT PARAMETERS</u>			<u>PLASMA OUTPUT</u>			
CURRENT (AMPS)	CAPILLARY RADIUS (mm)	CAPILLARY LENGTH (cm)	<u>POWELL</u>		<u>PPIB</u>	
			Temp. (K)	Resistance (mΩ)	Temp. (K)	Resistance (mΩ)
187,000	1.92	11.6	156,349	54.0	164,000	48
16,000	3.17	7.62	28,407	121.0	31,200	109
287,000	4.75	11.84	88,466	20.2	96,000	18
150,000	4.75	11.84	64,000	31.2	69,000	27
75,000	4.75	11.84	46,220	46.0	51,500	40

Table 2. Plasma Energy Partitioning for Three Test Cases With Varied Radii

CASE NO.	CAPILLARY RADIUS (mm)	PLASMA RESISTANCE* (m Ω)	<u>PLASMA ENERGY PARTITIONING (percent)</u>		
			<i>INTERNAL ENERGY</i>	<i>KINETIC ENERGY</i>	<i>WORK ENERGY</i>
1	1.92	138.3	66.5	11.2	22.3
2	4.75	48.6	73.0	9.0	18.0
3	7.00	31.8	75.0	8.4	16.6

*Plasma resistance for an input current amplitude of 75 kA and capillary length of 11.84 cm.

More calculations were performed to approximate the electrical transfer efficiency from the PFN by calculating the electrical efficiency for a fixed resistance load and a modified PFN providing a square current pulse. The power supply is modified as a "transmission line" type supply having inductors of a uniform value separating energy storage capacitors.

This arrangement is used for simplicity and to allow for a more direct method of determining its characteristic impedance. The characteristic impedance is now proportional to the square root of the ratio of total inductance to total capacitance and is calculated here at 146 m Ω . The resistance obtained from the plasma model (shown in Table 2) is now used by an electronic circuit analysis code to predict the electrical transfer efficiency. The resulting values are given in Table 3, column 3. This efficiency is now multiplied by the plasma partitioning percentage numbers in Table 2 to give the last three columns of numbers in Table 3 for plasma energy delivered from the PFN.

Finally, Table 4 provides a prediction from a black body radiation model showing the percentage of radiation belonging to each of the types of radiation.¹¹ Note that at the high internal plasma temperatures predicted, in all cases the majority of the energy is in the ultraviolet (UV) region. It is worth noting that similar internal (bulk) temperatures (3 eV) for capillaries of this size and input current level have been predicted by other researchers.¹² Assuming that all the energy in the plasma is radiative except for the kinetic energy component, then for Case 1, approximately 72.8% of the energy would be in the form of radiative energy.

Table 3. Percentage of delivered electrical energy from the pulsed power supply to plasma components of internal, kinetic, and work energies

CASE NO.	CAPILLARY RADIUS (mm)	PERCENT ENERGY DELIVERED FROM PFN*	<u>PERCENT ENERGY TRANSFERRED FROM PFN</u>		
			<i>INTERNAL ENERGY</i>	<i>KINETIC ENERGY</i>	<i>WORK ENERGY</i>
1	1.92	82 (1,361)	54.5 (905)	9.2 (153)	18.3 (304)
2	4.75	57 (946)	41.6 (691)	5.1 (85)	10.3 (171)
3	7.00	44 (730)	33.0 (548)	3.7 (61)	7.3 (121)

*For a square current pulse from a 2-MJ PFN with 1.66-MJ stored electrical energy having a characteristic impedance of 146 mΩ. The values in parantheses indicate the amount of energy, in kJ, obtained from the original 1.66 MJ of stored energy.

Table 4. Black Body Radiation Prediction for Three Plasma Test Cases

CASE NO.	RADIUS (mm)	PLASMA* TEMP. (K, eV)	<u>PLASMA RADIATION PARTITIONING (PERCENT)</u>		
			<i>UV</i> (0 - 0.3 micron)	<i>VISIBLE</i> (0.4 - 0.7 micron)	<i>INFRARED</i> (0.8 - 2 micron)
1	1.92	55,700, 4.8	97.8 (1,182)	2.1 (25)	0.1 (1.2)
2	4.75	34,232, 2.9	92.2 (795)	7.2 (62)	0.6 (5)
3	7.00	27,965, 2.4	87.5 (585)	11.4 (76)	1.1 (7)

* Similar plasma temperature results have been obtained from other plasma researchers (see Reference 12). The values in parantheses indicate the amount of energy, in kJ, obtained from the original 1.66 MJ of stored energy, assuming only internal and work energies contribute to radiation.

While this assumption is somewhat arbitrary and to be taken only as an approximation, it provides a simple way of accounting for energy losses encountered in the generation of the plasma. The results from this analysis indicate that, based on the approximated power supply efficiency and predicted internal plasma temperature for Case 1, of the original 1.66-MJ store of electrical energy, approximately 1.18 MJ are converted to ultraviolet energy. The remaining 27

kJ delivered to the plasma are shared by visible and infrared energy with about 25 kJ in the visible.

In addition, experimental work for the purpose of determining physical interaction of plasmas and propellants is progressing at ARL. In these studies, gun propellant samples are allowed to interact with the radiation from high energy plasmas, typical of those studied in this report. To date, the experimental results indicate a rapid optical reaction or response of the samples exposed to the plasma radiation.¹² These tests also show signs of increased propellant surface areas following plasma exposure and the importance of propellant location and geometry, all of which will also require further investigations.

3. SUMMARY

An electrothermal-chemical (ETC) gun model, designed by Princeton Combustion Research Laboratories (PCRL), for predicting the pulsed power, plasma, and interior ballistic aspects of an ETC gun system has been completed and delivered under contract to ARL. This model, PPIB, is configured as an end-to-end gun design code incorporating the three main subsystems of an ETC gun, based upon the well-known models of P2SIM, the Powell plasma model, and IBHVG2. This code has been validated against several sets of data, including pulsed power data from a 4-MJ system, 30-mm ETC plasma experiments, and the stand-alone version of the Powell plasma model.

The results from the one-dimensional Powell plasma model indicate that the capillary resistance is a sensitive function of input current and capillary radius. For the calculations performed here, the resistance varied by a factor of 4.3 over the range of radii used for a fixed current amplitude of 75 kA. The partitioning of energy into the various plasma constituents was shown to be fairly insensitive to changes in radius, changing at most by 8.5% over the range of radii used. However, for all capillary geometries and input electrical energies investigated, the predicted internal temperatures are quite high (between 2.4 and 4.8 eV). Similar internal plasma temperatures for capillaries of this size and input current level have also been predicted by other plasma researchers.¹² The generation of a high temperature plasma as seen in the test cases discussed here has the effect of converting most of the stored energy in the capacitor bank into ultraviolet radiation before the plasma expansion process. The usefulness of the ultraviolet radiation, how it changes or re-partitions during the combustion event, and how it reacts with materials such as gun propellants is not clear at the present time and will require further study. Also, experiments characterizing the plasma propellant interactions have been performed at ARL,

which indicate rapid optical reaction or response of sample propellants exposed to plasma radiation.¹³ These tests show signs of increasing propellant surface area following plasma exposure as well as the importance of propellant location and geometry, all of which will require further investigations.

INTENTIONALLY LEFT BLANK

REFERENCES

1. White, K.J., Oberle, W.F., Juhasz, A.A., Stobie, I.C., Nekula, K., Katulka, G.L., Driesen, S., "Electrothermal-Chemical Propulsion with High Loading Density Charges," U.S. Army Research Laboratory Technical Report, ARL-TR-845, Aberdeen Proving Ground, MD, August 1995.
2. Oberle, W.F., Stobie, I., DelGuercio, M., White, K., Bourham, M., and Gilligan, J. "Summary of Experimental Efforts to Determine Plasma Augmented Burn Rates for Solid Propellants," U.S. Army Research Laboratory Technical Report, ARL-TR-782, Aberdeen Proving Ground, MD, June 1995.
3. Princeton Combustion Research Laboratories, Inc, "Final Report: A Time-Dependent, Lumped-Parameter Power-Plasma-Interior Ballistics Code (PIIB) for Electrothermal-Chemical (ETC) Gun Performance Prediction," June 1995.
4. Princeton Combustion Research Laboratories, Inc, "Users Manual, P2SIM: A Time-Dependent, Lumped-Parameter Circuit Simulator For Electric Gun Leading Candidate Pulse-Power Systems," June 1993.
5. Powell, J.D., and Zielinski, A. E., "Theory and Experiment for an Ablating-Capillary Discharge and Application to Electrothermal-Chemical Guns," BRL-TR-3355, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1992.
6. Earnhart, J., Winsor, N., and Wren, G. "Electrothermal-Chemical Extensions to IBHVG2 With a New User's Tutorial," U.S. Army Research Laboratory Technical Report, ARL-TR-348, January 1994.
7. Spectrum Software, "Microcap III Users Manual," Sunnyvale, CA 1990.
8. Princeton Combustion Research Laboratories, Inc, "Final Report: P2SIM: A Time Dependent, Lumped Parameter Circuit Simulator For Electric Gun Leading Candidate Pulse Power Systems," June 1993.
9. Kurilenkov, Y.K., and Valuev, A.A. "The Electrical Conductivity of Plasma in Wide Range of Charge Densities," Beitr. Plasma Phys. 24, 161, 1984.
10. Katulka, G.L., Singh, D., Burdalski, R., "A 4-MJ Mobile Pulsed Power Facility for Electrothermal-Chemical Gun Applications," U.S. Army Research Laboratory Technical Report, ARL-TR-880, Aberdeen Proving Ground, MD, October 1995.
11. White, K. J., Private Communication, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, October 1995.

12. Jacob, E., Hermeline, F., Aussel, H., Bouquet, S., "Electrothermal Launcher Modeling in CEA," "Proceedings of the 5th European Symposium on Electromagnetic Launch Technology, April 1995.
13. White, K., Katulka, G., Driesen, S., "Electrothermal-Chemical Plasma Interaction with Propellants," 32nd JANNAF Combustion Subcommittee Meeting, Huntsville, AL, October 1995.

APPENDIX A
INPUT DECKS

INTENTIONALLY LEFT BLANK

1. P2SIM validation input deck

CONTROL 5uS 2 0
PULSE 5mS 1 10 10 1
ELEMENT CAPACITOR GENE 3 0 1 .99 0 1400.0uF 0mO 0 0 0 0 0 0 752 446072
ELEMENT CAPACITOR GENE 5 0 1 .99 0 1400.0uF 0mO 0 0 0 0 0 0 752 446072
ELEMENT CAPACITOR GENE 7 0 1 .99 0 1400.0uF 0mO 0 0 0 0 0 0 752 446072
ELEMENT CAPACITOR GENE 9 0 1 .99 0 1400.0uF 0mO 0 0 0 0 0 0 752 446072
ELEMENT CAPACITOR GENE 11 0 1 .99 0 1400.0uF 0mO 0 0 0 0 0 0 752 446072
ELEMENT INDUCTOR GENE 2 3 0 0. 0 120uH 10mO 0 0 0 47 56000
ELEMENT INDUCTOR GENE 4 5 0 0. 0 80uH 10mO 0 0 0 47 56000
ELEMENT INDUCTOR GENE 6 7 0 0. 0 60uH 10mO 0 0 0 47 56000
ELEMENT INDUCTOR GENE 8 9 0 0. 0 43uH 30mO 0 0 0 47 56000
ELEMENT INDUCTOR GENE 10 11 0 0. 0 30uH 10mO 0 0 0 47 56000 ELEMENT
RESISTOR GENE 1 0 0 0. 1 120mO
ELEMENT CLSWITCH GENE 1 2 0mS 10mO 0. 1MO 0 0 0 0 18 44000 ELEMENT
CLSWITCH GENE 1 4 0.5mS 10mO 0. 1MO 0 0 0 0 18 44000
ELEMENT CLSWITCH GENE 1 6 0.75mS 10mO 0. 1MO 0 0 0 0 18 44000
ELEMENT CLSWITCH GENE 1 8 1.0mS 10mO 0. 1MO 0 0 0 0 18 44000
ELEMENT CLSWITCH GENE 1 10 1.2mS 10mO 0. 1MO 0 0 0 0 18 44000
ELEMENT DIODE GENE 0 3 10V 45mO 0nH 1MO
ELEMENT DIODE GENE 0 5 10V 40mO 0nH 1MO ELEMENT DIODE GENE 0 7 10V
37mO 0nH 1MO ELEMENT DIODE GENE 0 9 10V 33mO 0nH 1MO ELEMENT DIODE
GENE 0 11 10V 30mO 0nH 1MO
ELEMENT BATTERY GENE 22KV 1000KJ 100uO 1nH 0 1KA 0 10Kg 1000. 1 ELEMENT
BATMOD GENE 0 0 0 1 1 0. 0

2. PPIB validation input deck for ARL five module PFN

```

CONTROL 5uS 2 0
PULSE 1mS 1 10 10 1
ELEMENT CAPACITOR GENE 3 0 1 .99 0 1020uF 0. 0. 0. 0. 0. 0. 0. 1. 1000. 1
ELEMENT CAPACITOR GENE 4 0 1 .99 0 488uF 0. 0. 0. 0. 0. 0. 0. 1. 1000. 1
ELEMENT CAPACITOR GENE 6 0 1 .99 0 615uF 0. 0. 0. 0. 0. 0. 0. 1. 1000. 1
ELEMENT CAPACITOR GENE 8 0 1 .99 0 195uF 0. 0. 0. 0. 0. 0. 0. 1. 1000. 1
ELEMENT CAPACITOR GENE 10 0 1 .99 0 400uF 0. 0. 0. 0. 0. 0. 0. 1. 1000. 1 ELEMENT
INDUCTOR GENE 1 2 0 0. 0 7uH 0. 0. 0. 0. 10. 1000. 1
ELEMENT INDUCTOR GENE 1 5 0 0. 0 16uH 0. 0. 0. 0. 10. 1000. 1
ELEMENT INDUCTOR GENE 1 7 0 0. 0 28uH 0. 0. 0. 0. 10. 1000. 1
ELEMENT INDUCTOR GENE 1 9 0 0. 0 58uH 0. 0. 0. 0. 10. 1000. 1
ELEMENT INDUCTOR GENE 1 11 0 0. 0 15uH 0. 0. 0. 0. 10. 1000. 1 ELEMENT
RESISTOR GENE 1 0 0 0. 1 35mO
ELEMENT CLSWITCH GENE 2 3 180uS 10uO 0. 1MO 0. 0. 0. 0. 10. 1000. 1
ELEMENT CLSWITCH GENE 5 4 120uS 10uO 0. 1MO 0. 0. 0. 0. 10. 1000. 1
ELEMENT CLSWITCH GENE 7 6 80uS 10uO 0. 1MO 0. 0. 0. 0. 10. 1000. 1
ELEMENT CLSWITCH GENE 9 8 40uS 10uO 0. 1MO 0. 0. 0. 0. 10. 1000. 1
ELEMENT CLSWITCH GENE 11 10 0uS 10uO 0. 1MO 0. 0. 0. 0. 10. 1000. 1
ELEMENT DIODE GENE 0 10 10V 10uO 0nH 1MO 0. 0. 0. 0. 1. 1000. 1 ELEMENT
DIODE GENE 0 8 10V 10uO 0nH 1MO 0. 0. 0. 0. 1. 1000. 1
ELEMENT DIODE GENE 0 6 10V 10uO 0nH 1MO 0. 0. 0. 0. 1. 1000. 1
ELEMENT DIODE GENE 0 4 10V 10uO 0nH 1MO 0. 0. 0. 0. 1. 1000. 1
ELEMENT DIODE GENE 0 3 10V 10uO 0nH 1MO 0. 0. 0. 0. 1. 1000. 1
ELEMENT BATTERY GENE 7KV 1000KJ 100uO 1nH 0 1KA 0 10Kg 1000. 1
ELEMENT BATMOD GENE 0 0 0 1 1 0. 0

```

3. PPIB plasma capillary input deck

```
4.74E-03,101,10.92E-2,0,1
400,401,1,1 0.5,0.1,0.2,1.0E4,273.,1.0E-04,.001,6.173e7 1.0,1.00E-5
1 13 3 2
2.0 0.00
1.0 0.00
3.0 16.4
5.0 43.5
5.0 10193.70
1.0 21648.4
5.0 33735.2
9.0 60360.0
3.0 61982.0
15.0 64091.0
3.0 68858.0
15.0 69715.0
3.0 70744.0
9.0 71368.0
2.0 0.00
4.0 64.0
12.0 43024.0
1.0 0.00
9.0 52349.0

0.
0.9
1.,1.,1.
5
0. .25 .5 .75 1.
1.,0.,0.
C RI,NZ,XL,IOPT
C ITMAX,IPRINT,ICHOKE,ICALC
C X1C,X2C,X1H,CON,T,XLAM,TCUT,RCUT
C PARTITION FUNCTION DATA
C PEX
```

4. PPIB plasma capillary input deck (table 1 data)

4.75D-03,101,11.84D-2,0,1
400,401,1,1 0.5,0.1,0.2,1.0D4,273.,1.0D-04,.001,6.173D7 1.0,1.0D-5
1 13 3 2
2.0 0.00
1.0 0.00
3.0 16.4
5.0 43.5
5.0 10193.70
1.0 21648.4
5.0 33735.2
9.0 60360.0
3.0 61982.0
15.0 64091.0
3.0 68858.0
15.0 69715.0
3.0 70744.0
9.0 71368.0
2.0 0.00
4.0 64.0
12.0 43024.0
1.0 0.00
9.0 52349.0
0.
0.9
5
0. .25 .5 .75 1.
1.,1.,1.
C RI,NZ,XL,IOPT
C ITMAX,IPRINT,ICHOKE,ICALC
C X1C,X2C,X1H,CON,T,XLAM,TCUT,RCUT
C PARTITION FUNCTION DATA
C PEX

NO. OF
COPIES ORGANIZATION

2 ADMINISTRATOR
DEFENSE TECHNICAL INFO CENTER
ATTN DTIC DDA
8725 JOHN J KINGMAN RD STE 0944
FT BELVOIR VA 22060-6218

1 COMMANDER
US ARMY MATERIEL COMMAND
ATTN AMCAM
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL OP SD TA/
RECORDS MANAGEMENT
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL OP SD TL/
TECHNICAL LIBRARY
2800 POWDER MILL RD
ADELPHI MD 207830-1197

1 DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL OP SD TP/
TECH PUBLISHING BRANCH
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 COMMANDER
USA ARDEC
ATTN SMCAR WAH T J DOMEN
BLDG 62 NORTH
PCTNY ARSNL NJ 07806-5000

1 COMMANDER
USA ARDEC
ATTN SMCAR AEE BR K KLINGAMAN
BLDG 1501
PCTNY ARSNL NJ 07806-5000

1 DIRECTOR
USA BMD
ADV TECH CTR
PO BOX 1500
HUNTSVILLE AL 35807

NO. OF
COPIES ORGANIZATION

1 CHAIRMAN
DOD EXP SAFETY BD
RM 856 C HOFFMAN BLDG 1
2461 EISENHOWER AVE
ALEXANDRIA VA 22331-0600

1 DA OFC OF PM
155MM HWTZR M109A6 PALADIN
ATTN SFAE AR HIP IP
R DE KLEINE
PCTNY ARSNL NJ 07806-5000

1 COMMANDER
USA ARDEC
ATTN AMSMC PBM E L LAIBSON
PCTNY ARSNL NJ 07806-5000

3 PEO ARMAMENTS PM TMAS
ATTN AMCPM TMA K RUSSELL
AMCPM TMA 105
AMCPM TMA 120
PCTNY ARSNL NJ 07805-5000

2 DIRECTOR
BENET LAB USA WATERVLIET ARNSL
ATTN SARWV RD G CARAFANO
R HASOENBEIN
WATERVLIET NY 12189

2 DIRECTOR
BENET LAB USA WATERVLIET ARNSL
ATTN SARWV RD P VOTIS
M CIPOLLO
WATERVLIET NY 12189

1 COMMANDER
USA AMCCOM
ATTN AMSMC IRC G COWAN
SMCAR ESM R W FORTUNE
R ZASTROW
ROCK ISLAND IL 61299-7300

2 COMMANDER
USA AMCCOM
ATTN SMCAR ESM R W FORTUNE
R ZASTROW
ROCK ISLAND IL 61299-7300

1 COMMANDER
USA CECOM
ATTN ASQNC ELC ISL R
R&D TECH LIB MYER CTR
FT MONMOUTH NJ 07703-5301

NO. OF
COPIES ORGANIZATION

1 COMMANDANT
 USA AS
 ATTN AVIATION AGENCY
 FT RUCKER AL 36360

1 DIRECTOR
 HQ TRAC RPD
 ATTN ATCD MA MAJ WILLIAMS
 FT MONROE VA 23651-5143

1 HQ USAMC
 ATTN AMCICP AD
 M F FISETTE
 5001 EISENHOWER AVE
 ALEXANDRIA VA 22333-0001

2 COMMANDER
 USA ARDEC
 ATTN SMCAR CCD D SPRING
 SMCAR CCS
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR CCH T L ROSENDORG
 SMCAR CCH V E FENNELL
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR AEE B D DOWNS
 P CHIU
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR AEE J LANNON
 SMCAR AED S KAPLOWITZ
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR FSA T M SALSBUY
 T GORA
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR B KNUTELSKY
 A GRAF
 PCTNY ARSNL NJ 07806-5000

NO. OF
COPIES ORGANIZATION

1 COMMANDER
 USA ARDEC
 ATTN SMCAR
 K CHEUNG
 PCTNY ARSNL NJ 07806-5000

2 COMMANDER
 USA ARDEC
 ATTN SMCAR EG G FERDINAND
 R ZIMANY
 PCTNY ARSNL NJ 07806-5000

1 US ARMY RSCH LAB
 ATTN AMSRL WT N
 J INGRAM
 2800 POWDER MILL RD
 ADELPHI MD 20783-1197

1 US ARMY RSCH LAB
 ATTNAMSRL WT NH
 J CORRIGAN
 2800 POWDER MILL RD
 ADELPHI MD 20783-1145

1 US ARMY RSCH LAB
 ATTN AMSRL WT NG
 T OLDHAM
 2800 POWDER MILL RD
 ADELPHI MD 20783-1145

1 US ARMY RSCH LAB
 ATTN AMSRL EP MC
 D SINGH
 BLDG 2707
 FT MONMOUTH NJ 07703-5000

2 COMMANDER
 USARO
 ATTN TECH LIB D MANN
 PO BOX 12211
 RSCH TRI PK NC 27709-2211

1 COMMANDER
 USABRDEC
 ATTN STRBE WC TECH LIB VAULT
 BLDG 315
 FT BELVOIR VA 22060-5606

1 COMMANDER
 USA TRAC FT LEE
 DEFENSE LOGISTICS STUDIES
 FT LEE VA 23801-6140

NO. OF
COPIES ORGANIZATION

1 PRESIDENT
USA ARTILLERY BD
FT SILL OK 73503

1 COMMANDANT
USACGSC
FT LVN WORTH KS 66027-5200

1 COMMANDANT
USASWS
ATTN REV & TNG LIT DIV
FT BRAGG NC 28307

1 COMMANDER
RADFORD ARMY AMMO PLANT
ATTN SMCRA QA HI LIBRARY
RADFORD VA 24141

1 COMMANDANT
USAFAS
ATTN STSF TSM CN
FT SILL OK 73505-5600

1 DEP CDR SDC
ATTN SFAE SD HVL
D LIANOS
PO BOX 1500
HUNTSVILLE AL 35887-8801

3 COMMANDER
USA FSTC
ATTN AMSCT MC 3 S LEBEAU
C BEITER
220 SEVENTH ST NE
CHARLOTTESVILLE VA 22901

1 COMMANDANT
USA FACS
ATTN ATSF CO MW
B WILLIS
FT SILL OK 73503

1 OFC NAVAL RSCH
ATTN CODE 473 R S MILLER
800 N QUINCY ST
ARLINGTON VA 22217

2 COMMANDER
NSSC
ATTN SEA 62R
SEA 64
WASHINGTON DC 20362-5101

NO. OF
COPIES ORGANIZATION

1 COMMANDER
NASC
ATTN AIR 954 TECH LIB
WASHINGTON DC 20360

1 NAVAL RSCH LAB
TECH LIB
WASHINGTON DC 20375

2 COMMANDER
HSWC
ATTN J P CONSAGA
C GOTZMER
SLVR SPRNG MD 20902-5000

2 COMMANDER
NSWC
ATTN CODE R13 K KIM
CODE R13 R BERNECKER
SLVR SPRNG MD 20902-5000

3 CDR NSWC INDIAN HEAD DIV
ATTN 6210 C SMITH
6210J K RICE
6210C S PETERS
INDIAN HEAD MD 20640-5035

3 CDR NSWC DAHLGREN DIV
ATTN CODE G33 T DORAN
J COPLEY
CODE G30 G&M DIV
DAHLGREN VA 2448-5000

3 CDR NSWC DAHLGREN DIV
ATTN CODE G301 D WILSON
CODE G32 GUNS SYSTEMS DIV
CODE E23 TECH LIB
DAHLGREN VA 2448-5000

1 CDR NSWC CRANE DIV
ATTN CODE 4052 S BACKER
BLDG 108
CRANE IN 47522-5000

2 CDR NUSC ENG CONV DEPT
ATTN CODE 5B331 R S LAZAR
TECH LIB
NEWPORT RI 02840

1 CDR NSWC INDIAN HD DIV
ATTN CODE 270P1 MR E CHAN
101 STRAUS AVE
INDIAN HEAD MD 20640

NO. OF
COPIES ORGANIZATION

1 CDR NSWC INDIAN HD DIV
ATTN CODE 3120 MR R RAST
101 STRAUS AVE
INDIAN HEAD MD 20640

1 CDR NSWC INDIAN HD DIV
ATTN CODE 210P1 R SIMMONS
101 STRAUS AVE
INDIAN HEAD MD 20640

2 CDR NSWC INDIAN HD DIV
ATTN CODE 6210 S BOYLES
N ALMEYDA
101 STRAUS AVE
INDIAN HEAD MD 20640

1 CCDR NAWC
ATTN CODE 3891 A ATWOOD
CHINA LAKE CA 93555

1 CDR USAARDEC
ATTN SMCAR CCH J HEDDERICH
BLDG 1
PCTNY ARNSL NJ 07806-5000

1 OLAC PL TSTL
ATTN D SHIPLETT
EDWARD AFB CA 93523-5000

10 CIA
OFC OF CENTRAL REFERENCE
DISSEMINATION BRANCH
RM GE47 HQS
WASHINGTON DC 20502

1 CIA
ATTN J E BACKOFEN
HQ RM 5F22
WASHINGTON DC 20505

3 DIRECTOR LANL
ATTN B KASWHIA
H DAVIS
E526 W REASS
LOS ALAMOS NM 87545

1 DIRE LLNL
ATTN MS L355 A BUCKINGHAM
PO BOX 808
LIVERMORE CA 94550

NO. OF
COPIES ORGANIZATION

1 DIR SANDIA NAT LAB
COMBUSTION RSCH FACILITY
ATTN R ARMSTRONG
DIV 8357
LIVERMORE CA 94551-0469

1 DIR SANDIA NAT LAB
COMBUSTION RSCH FACILITY
ATTNS VOSEN
DIV 8357
LIVERMORE CA 94551-0469

1 UNIVERSITY OF ILLINOIS
DEPT OF MECH INDUST ENGR
ATTN PROF H KRIER 144 MEB
1206 N GREEN ST
URBANA IL 61801

1 JHU CPIA
ATTN T CHRISTIAN
10630 LTLE PATUXENT PKWY
STE 202
COLUMBIA MD 21044-3200

2 PENN STATE UNIV
DEPT OF MECHANICAL ENGR
ATTN J BROWN
312 MECHANICAL ENGR BLDG
UNIVERSITY PK PA 16802

1 NCSU
ATTN J G GILLIGAN
BOX 7909
1110 BURLINGTON ENGR LABS
RALEIGH NC 27695-7909

1 NCSU
ATTN M BOURHAM
BOX 7909
1110 BURLINGTON ENGR LABS
RALEIGH NC 27695-7909

2 INST FOR ADV TECH
ATTN DR H FAIR
P SULLIVAN
4030 2 W BAKER LANE
AUSTIN TX 78759-5329

1 INST FOR ADV TECH
ATTN DR I MCNAB
4030 2 W BAKER LANE
AUSTIN TX 78759-5329

NO. OF
COPIES ORGANIZATION

1 SRI INTERNATIONAL
PROPULSION SCIENCE DIV
ATTN TECH LIB
333 RAVENSWOOD AVE
MENLO PARK CA 94025

1 SPARTA
ATTN DR M HOLLAND
945 TOWNE CENTER DR
SAN DIEGO CA 92121-1964

2 UNITED DEFENSE
ATTN MR M SEALE
DR A GIOVANETTI
4800 E RIVER RD
MINNEAPOLIS MN 55421-1498

1 UNITED DEFENSE
ATTN MR J DYVIK
4800 E RIVER RD
MINNEAPOLIS MN 55421-1498

1 HERCULES INC
RADFORD ARMY AMMO PLANT
ATTN D A WORRELL
PO BOX 1
RADFORD VA 24141

1 HERCULES INC
RADFORD ARMY AMMO PLANT
ATTN E SANFORD
PO BOX 1
RADFORD VA 24141

2 GDLS
ATTN MR F LUNSFORD
DR M WEIDNER
PO BOX 2074
WARREN MI 48090-2074

2 OLIN ORDNANCE
ATTN V MCDONALD LIBRARY
H MCELROY
PO BOX 222
ST MARKS FL 32355

1 OLIN ORDNANCE
ATTN D WORTHINGTON
PO BOX 222
ST MARKS FL 32355

1 PAUL GOUGH ASSOC INC
ATTN P S GOUGH
1048 SOUTH ST
PORTSMOUTH NH 03801-5423

NO. OF
COPIES ORGANIZATION

1 PHYSICS INTL LIBRARY
ATTN H W WAMPLER
PO BOX 5010
SAN LEANDRO CA 94577-0599

1 ROCKWELL INTL
ROCKETDYNE DIV
ATTN BA08 J E FLANAGAN
6633 CANOGA AVE
CANOGA PK CA 91304

1 ROCKWELL INTL
ROCKETDYNE DIV
ATTN BA08 J GRAY
6633 CANOGA AVE
CANOGA PK CA 91304

1 SCIENCE APPLICATIONS INC
ATTN J BATTEH
1225 JOHNSON FERRY RD
STE 100
MARIETTA GA 30068

1 SCIENCE APPLICATIONS INC
ATTN L THORNHILL
1225 JOHNSON FERRY RD
STE 100
MARIETTA GA 30068

1 ELI FREEDMAN & ASSOC
ATTN E FREEDMAN
2411 DIANA RD
BALTIMORE MD 21209

1 VERITAY TECH INC
ATTN MR E FISHER
4845 MILLERSPORT HWY
E AMHERST NY 14051-0305

1 BATTELLE
ATTN TACTEC LIB
J N HUGGINS
505 KING AVE
COLUMBUS OH 43201-2693

1 CA INSTITUTE OF TECH
JET PROPULSION LAB
ATTN L D STRAND MS125 224
4800 OAK GROVE DR
PASADENA CA 91109

NO. OF
COPIES ORGANIZATION

1 CA INSTITUTE OF TECH
JET PROPULSION LAB
ATTN D ELLIOT
4800 OAK GROVE DR
PASADENA CA 91109

1 USA BENET LAB
ATTN SMCAR CCB R
DR DR S SPOCK
WATERVLIET NY 12189

1 MARTIN MARIETTA DEFENSE SYS
ATTN DR J MANDZY
MAIL DROP 42 220
100 PLASTICS AVE
PITTSFIELD MA 01201

1 STATE U OF NY
DEPT OF ELEC ENGR
ATTN DR W J SARGEANT
BONNER HALL RM 312
BUFFALO NY 14260

1 TEXAS TECH UNIVERSITY
DEPT OF EE COMPUTER SCIENCE
ATTN DR M KRISTIANSEN
LUBBOCK TX 79409-4439

1 UNIV OF TEXAS AT ARLINGTON
DEPT OF ELEC ENGR
ATT DR L GORDON
BOX 19016
ARLINGTON TX 76019-0016

1 WILKES UNIVERSITY
DEPT OF ELEC ENGR
ATTN DR A ARMAND
WILKES BARRE PA 18766

2 UNIVERSITY OF DELAWARE
DEPT OF ELEC ENGR
ATTN DR N GALLAGHER
DR J KOLODZEY
NEWARK DE 19716

1 COLORADO SCHOOL OF MINES
DEPT OF ENGINEERING
ATTN C BRAUN
GOLDEN CO 80401

1 SNL
ATTN MR M GRUBELICH
DIV 2515
PO BOX 5800
ALBUQUERQUE NM 87185

NO. OF
COPIES ORGANIZATION

2 LOCKHEED MARTIN DEF SYSTEMS
PRINCETON COMBUSTION RSCH LABS
ATTN N A MESSINA
11 DEER PARK DR BLDG IV SUITE 119
MONMOUTH JUNCTION NJ 08852

1 COMMANDER USA ARDEC
ATTN SFAE ASM TMA AS
R BILLINGTON
PICATINNY ARSENAL NJ 07806-5000

2 RARDE
GS2 DIVISION BLDG R31
ATTN DR C WOODLEY, DR G COOK
FORT HALSTEAD
SEVENOAKS KENT TN14 7BP
ENGLAND

1 MATERIALS RESEARCH LABORATORY
SALISBURY BRANCH
ATTN ANNA WILDEGGER GAISSMAIER
EXPLOSIVES ORDNANCE DIVISION
SALISBURY
SOUTH AUSTRALIA 5108

ABERDEEN PROVING GROUND

5 DIR ARL
ATTN AMSRL OP AP L (TECH LIB)
BLDG 305 APG

5 CDR USAATC
ATTN WALTON
G RICE
D LACEY
C HERUD
STECS DA ID
L FRANCIS

36 DIR USARL
ATTN AMSRL WT I MAY
J ROCCHIO
D ECCLESHALL
AMSRL WT P A HORST
E SCHMIDT
P KASTE
AMSRL WT PC B FORCHE
R PESCE-RODRIGUEZ
AMSRL WT PB P PLOSTINS
D LYON
A ZIELINSKI
AMSRL WT PD B BURNS
AMSRL WT PA T MINOR
M DEL GUERCIO
J DESPIRITO

NO. OF
COPIES ORGANIZATION

A JUHASZ
 J KNAPTON
 G KATULKA (5 CYS)
 G KELLER
 P CONROY
 D KOOKER
 W OBERLE
 C RUTH
 T ROSENBERGER
 I STOBIE
 P TRAN
 K WHITE
 G WREN
 M MCQUAID
 AMSRL WT T W MORRISON
 AMSRL WT W C MURPHY
 AMSRL WT WB W D'AMICO
 AMSRL WT WD
 A NIILER
 C HOLLANDSWORTH
 J POWELL